

**50313006**

## Hexagonal insulator Height 30 M6 female to female



Insulating busbar supports to mount copper or aluminium busbars, tested to hold them securely during a short circuit.

### Strong points

- Insulating materials
- Durability
- Adaptability

### General characteristics

- Polyester without halogen.
- UL94 VO self-extinguishing.
- Colour red RAL 3002.
- Operating temperature -40°C to +130°C.
- Deformation under load temperature (ASTM D643): > 200°C.
- Dielectric constant (ASTM D150): 4/5.
- Arc resistance (ASTM D495): > 180 s.
- Water absorption (ASTM D570):

### Compliance with standards

- IEC 61439-1
- IEC 60865-1

### Link to the reference



<https://www.socomec.us/en-us/reference/50313006>

### Standards

Conformity to standards	IEC
-------------------------	-----

### Technical Characteristics

Height [mm]	30
Width [mm]	33
Depth [mm]	33
Weight [kg]	0.042
Diameter	M6
Rated voltage	1000 Vac
Type	Hexagonal

### ETIM - Electrical characteristics

Number of poles	1
-----------------	---

### Logistics

GTIN/EAN	3596031723898
Customs number	8546901000
Price unit	PC
Weight of the packing unit [kg]	0.042
Length of the packing unit [m]	0.035
Width of the packing unit [m]	0.04
Depth of the packing unit [m]	0.03

### Product Details

Effective date	2003-11-26
Offer Life Cycle Code	40
Country of origin	IN

### Classification

UNSPSC	39121321
ETIM Class	EC001166
IGCC	4462