

Torque screwdriver TorqueVario®-S variably adjustable torque limit 0.1 - 0.6 (36850)



wiha 

Tools that work for you

Wiha Werkzeuge GmbH
Obertalstraße 3-7 78136
Schonach
E-Mail: info.de@wiha.com
Tel.: +49 (0)7722 959-0

Order no.: 36850

Article number: 2852106001

EAN: 4010995368500

Customs tariff number: 82054000

Meets your requirements: Variably adjustable torque covers a wide range of applications.

Increases your efficiency: The correct torque protects material from damage and means no follow-up work.

Protects your health: With the patented SoftFinish® handle design, ensuring work is kind to hands and muscles. Recommended by doctors and therapists at German Campaign for Healthier Backs.

Lowers your costs: The correct torque protects you from warranty claims.

Application: For applications where recommended torque settings are important. Use in combination with a Wiha torque interchangeable blade.

Extra: Incl. works inspection protocol.

Extra: Delivered in practical plastic box.

Accuracy: $\pm 6\%$, tracing to national standards (see table for other tolerances).

Handle: Torque infinitely adjustable with Torque-Setter setting tool (also supplied).

Handle: Ergonomic multi-component handle, particularly light and compact.

Handle: Handle sizes proportioned to optimise torque setting.

Handle: Audible and perceptible click when the pre-set torque has been attained.

Handle: Compatible with all blades of the 2859.

Bit holders or blades are not included in delivery.

DIN EN ISO 6789.

Customs tariff number	82054000
-----------------------	----------

Tolerance	6 %
-----------	-----

Torque range min (Nm)	0.1 Nm
-----------------------	--------

Torque range max (Nm)	0.6 Nm
-----------------------	--------

Self service - packing	No
------------------------	----

Handle diameter	23 mm
-----------------	-------

Hexagon head (mm)	4.0 mm
-------------------	--------

Handle length	127 mm
---------------	--------

Tool for electricians	No
-----------------------	----

Country of origin (ISO 3166-1 Alpha 3)	DEU
----------------------------------------	-----
